

PROLINE™ SERIES

MID-SIZE MOWERS

NEW

**TIME SAVER.
MONEY MAKER.**



Contractors know every second not mowing is a lost opportunity, and training your crew on new equipment can cause unnecessary setbacks in time and money.

MAXIMIZE YOUR EFFICIENCY with the Toro PROLINE mid-size mowers. Not only will your crew be mowing in no time with easy-to-learn controls, but you'll also enjoy top-line reliability and professional cutting performance.

YOU'LL LOVE THE CONVENIENCE of the 2-wheel sulky, which rotates 360° and simply folds away when not in use; no more attaching and removing when trailering! Sold separately.

AND YOU CAN REST EASY knowing that Toro stands behind its mowers with a 3-year, 750-hour warranty.

TORO®

| | 44410 44409 CARB Model | 44424 44423 CARB Model | 44427 | 44430 | 44436† | 44448† | 44454† | 44460† | | | | | | | | |
|---------------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|----------|----------|----------|----------|----------|----------|----------|----------|
| POWER SYSTEM | | | | | | | | | | | | | | | | |
| Commercial Engines at 3600 RPM* | 14.5 hp Kawasaki® FS | ▶ 15 hp Kawasaki FS | ▶ 18.5 hp Kawasaki FS | ▶ 22 hp Kawasaki FS | 15.5 hp Kawasaki FX | 22 hp Kawasaki FX | 22 hp Kawasaki FX | 22 hp Kawasaki FX | | | | | | | | |
| Starter | Electric | Electric | Electric | Electric | Electric | Electric | Electric | Electric | | | | | | | | |
| Drive Tires | 18" | ▶ 20" | 20" | 20" | 18" | ▶ 20" | 20" | 20" | | | | | | | | |
| Caster Tires | 9" | ▶ 11" | 11" | 11" | 9" | 11" | 11" | 11" | | | | | | | | |
| Fuel/Capacity | Gas / 5 Gal (18.9 L) | Gas / 5 Gal (18.9 L) | Gas / 5 Gal (18.9 L) | Gas / 5 Gal (18.9 L) | Gas / 5 Gal (18.9 L) | Gas / 5 Gal (18.9 L) | Gas / 5 Gal (18.9 L) | Gas / 5 Gal (18.9 L) | | | | | | | | |
| Control System | Twin Lever | Twin Lever | Twin Lever | Twin Lever | Twin Lever | Twin Lever | Twin Lever | Twin Lever | | | | | | | | |
| Transmission | ZT-2800 | ZT-2800 | ZT-2800 | ZT-2800 | ▶ ZT-3100 | ZT-3100 | ZT-3100 | ZT-3100 | | | | | | | | |
| Hour Meter | Standard | Standard | Standard | Standard | Standard | Standard | Standard | Standard | | | | | | | | |
| Maximum Forward Speed | 7 mph (11.3 km/h) | 7 mph (11.3 km/h) | 7 mph (11.3 km/h) | 7 mph (11.3 km/h) | 7 mph (11.3 km/h) | 7 mph (11.3 km/h) | 7 mph (11.3 km/h) | 7 mph (11.3 km/h) | | | | | | | | |
| Brake System | Integrated Parking Brake | Integrated Parking Brake | Integrated Parking Brake | Integrated Parking Brake | Integrated Parking Brake | Integrated Parking Brake | Integrated Parking Brake | Integrated Parking Brake | | | | | | | | |
| MOWING DECKS | | | | | | | | | | | | | | | | |
| Deck Size | 36" (91.4 cm) | ▶ 48" (121.9 cm) | ▶ 54" (137.2 cm) | ▶ 60" (152.4 cm) | 36" (91.4 cm) | ▶ 48" (121.9 cm) | ▶ 54" (137.2 cm) | ▶ 60" (152.4 cm) | | | | | | | | |
| Cutting Deck | 10-Gauge Steel | 10-Gauge Steel | 10-Gauge Steel | 10-Gauge Steel | 7/10-Gauge Steel | 7/10-Gauge Steel | 7/10-Gauge Steel | 7/10-Gauge Steel | | | | | | | | |
| Bullnose Bumper | Standard | Standard | Standard | Standard | Standard | Standard | Standard | Standard | | | | | | | | |
| Adjustable Discharge Baffle | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | | | | | | | | |
| Rubber Discharge Chute | - | - | - | - | ▶ Standard | Standard | Standard | Standard | | | | | | | | |
| Deck Lift Assist | Standard | Standard | Standard | Standard | Standard | Standard | Standard | Standard | | | | | | | | |
| Spindle Housings | 8" Cast Aluminum | 8" Cast Aluminum | 8" Cast Aluminum | 8" Cast Aluminum | 8" Cast Aluminum | 8" Cast Aluminum | 8" Cast Aluminum | 8" Cast Aluminum | | | | | | | | |
| Spindle Bearings | Maintenance Free | Maintenance Free | Maintenance Free | Maintenance Free | Maintenance Free | Maintenance Free | Maintenance Free | Maintenance Free | | | | | | | | |
| Cutting Height | 1.5" – 4.5" (3.8 – 11.4 cm) | 1.5" – 4.5" (3.8 – 11.4 cm) | 1.5" – 4.5" (3.8 – 11.4 cm) | 1.5" – 4.5" (3.8 – 11.4 cm) | 1.5" – 4.5" (3.8 – 11.4 cm) | 1.5" – 4.5" (3.8 – 11.4 cm) | 1.5" – 4.5" (3.8 – 11.4 cm) | 1.5" – 4.5" (3.8 – 11.4 cm) | | | | | | | | |
| Blades | .204" Heat-Treated Steel | .204" Heat-Treated Steel | .204" Heat-Treated Steel | .204" Heat-Treated Steel | .204" Heat-Treated Steel | .204" Heat-Treated Steel | .204" Heat-Treated Steel | .204" Heat-Treated Steel | | | | | | | | |
| Blade Tip Speed | 18,500+ ft./min. | 18,500+ ft./min. | 18,500+ ft./min. | 18,500+ ft./min. | 18,500+ ft./min. | 18,500+ ft./min. | 18,500+ ft./min. | 18,500+ ft./min. | | | | | | | | |
| Belt Construction | Aramid Fiber V-Belt | Aramid Fiber V-Belt | Aramid Fiber V-Belt | Aramid Fiber V-Belt | Aramid Fiber V-Belt | Aramid Fiber V-Belt | Aramid Fiber V-Belt | Aramid Fiber V-Belt | | | | | | | | |
| Anti-Scalp Rollers | Standard | Standard | Standard | Standard | Standard | Standard | Standard | Standard | | | | | | | | |
| WEIGHTS AND MEASUREMENTS | | | | | | | | | | | | | | | | |
| Weight | 580 lbs. | 263.1 kg | 639 lbs. | 289.8 kg | 648 lbs. | 294.9 kg | 693 lbs. | 314.3 kg | 608 lbs. | 275.8 kg | 669 lbs. | 303.5 kg | 695 lbs. | 315.2 kg | 730 lbs. | 331.1 kg |
| Height | 45" | 114.3 cm | 46" | 116.8 cm | 46" | 116.8 cm | 46" | 116.8 cm | 45" | 114.3 cm | 46" | 116.8 cm | 46" | 116.8 cm | 46" | 116.8 cm |
| Deck Clearance Width | 37" | 94.0 cm | 49" | 124.5 cm | 55" | 139.7 cm | 61" | 154.9 cm | 37" | 94.0 cm | 49" | 124.5 cm | 55" | 139.7 cm | 61" | 154.9 cm |
| Deflector Width | 51" | 129.5 cm | 63" | 160.0 cm | 69" | 175.3 cm | 75" | 190.5 cm | 51" | 129.5 cm | 63" | 160.0 cm | 69" | 175.3 cm | 75" | 190.5 cm |
| Length | 77" | 195.6 cm | 80" | 203.2 cm | 80" | 203.2 cm | 83" | 210.8 cm | 77" | 195.6 cm | 80" | 203.2 cm | 80" | 203.2 cm | 83" | 210.8 cm |

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

†CARB compliant model or model available.



DRIVE WITH EASE

Shred grass in no time with the easy-to-learn twin-lever controls and drive assist with three settings.

MOWING MUSCLE

Ensure you never lose a job because of broken equipment with a reliable Kawasaki engine that drives .204" blades for a gorgeous, professional cut.

MADE TO LAST

Your Toro is also built to take on years of rough rides with a bull nose bumper and 20" wheels with curb clearance.

QUICK ADJUSTMENT

Changing cut lengths on the go is a snap with a single-point height of cut adjustment.

NO-HASSLE SULKY

The 2-wheel sulky simply folds away, meaning no need to attach and remove it when trailering. *Sold separately.*